

EAT•N

Powerware

APR24 Access Power Rectifier



Features

- Fast On-Line Replacement of Rectifiers (Hot-Swap)
- Automatic Set-up from Supervisory Module
- Intelligent microprocessor controlled
- High Power Density
- High Efficiency and Unity Power Factor
- Wide AC Supply Conditions
- Wide Output Voltage Ranges
- Constant Power Output
- Compliance with International Standards

The Powerware APR24 series of 24V rectifier modules are designed specifically for network access applications such as customer premises equipment, and road-side cabinet installations.

The combination of leading high frequency switch mode technology with high reliability fan cooling makes the APR24 a flexible, efficient, and reliable DC power source.

Designed for operation at up to 70°C (158°F) and under a wide range of AC power conditions means that the APR24 is perfectly suited to the demanding environments found in network access applications.

With up to 88% efficiency, optimum performance at typical load currents, and power factor correction the APR24 has some of the lowest running costs for any 24V DC power system of its type available.

Designed to operate with the Powerware SM40/SM45 and SM60/SM65 supervisory modules in any of the versatile Access Power Solutions DC power systems the APR24 rectifier modules will provide years of cost-effective, and trouble free service for your network access equipment.

Technical Specifications

Brief Technical Specifications

AC Supply	220/240V, 50/60Hz (nominal) 185V-275V: full output up to 50°C [122°F] 150V-185V: full output up to 30°C [86°F]
Power Factor	>0.99 (50 – 100% Output Current)
Efficiency	88% (50 – 100% Output Current)
DC Output Voltage Range	24V: 21.5 – 29V
DC Output (maximum)	750W, 31A @ 24V
Operating Temperature Range	-40°C – +70°C [-40°F – +158°F]
Output current is derated above 50°C [122°F] and below -10°C [14°F]	
Cooling	Temperature controlled, high reliability fan
Dimensions H,W,D	3U: 133mm [5.25"], 13E: 66mm [2.6"], 280mm [11"] overall
Weight	1.9kg [4.2lb]

Certifications

All products comply with International Standards. Contact your local Powerware DC representative for details on the specific product versions available with these safety and EMC approvals:

North America	UL, FCC Verification, CSA, IC
Europe	CE
Australia / New Zealand	C-tick, Telepermit

In the interests of continual product improvement all specifications are subject to change without notice.